

### APPLICATION AREAS

Playgrounds and  
Walking Paths

### SYSTEM DESCRIPTION

"Anymats Rt - Modular Rubber"  
100% Recycled  
SBR granules and rubber  
blends are mixed with special  
polyurethane adhesive and  
produced by press method in  
suitable temperature and  
pressure molds

### FEATURES

Due to its special texture  
on the surface,  
it minimizes slippage and  
provides considerable  
comfort in walking areas  
and children's  
play areas.

## ANYMATS RT - MODULAR RUBBER

### TECHNICAL INFORMATION

20 MM	40x40 CM	17.50 KG/M2
25 MM	40x40 CM	22.00 KG/M2
30 MM	40x40 CM	26.50 KG/M2
40 MM	40x40 CM	34.00 KG/M2
25 MM	50x50 CM	22.00 KG/M2
30 MM	50x50 CM	26.50 KG/M2
40 MM	50x50 CM	34.00 KG/M2

### TECHNICAL VALUES

<b>Critical Height of Drop</b>	0,94 M (HIC Coefficient- TSE General Security Rules)
<b>Flammability</b>	76 / 769 / EEC Compliance with Directives
<b>Abrasion</b>	0,036 µm
<b>Endurance</b>	19,18 Mpa / cm <sup>2</sup>
<b>Water Permeability</b>	%1,85
<b>Density</b>	0,910 gr/cm <sup>3</sup>
<b>Resistance to Cigarette</b>	TS 11900 EN 1399 Compliance with Norms

### APPLICATION METHOD

<b>PU Glue</b>	Double component glue is mixed. Approximately 1.00 KG / m2 is applied with a treaded trowel between 30 and 40 minutes.
<b>Modular Rubber</b>	The modular rubbers are lined up side by side at desired pattern so that there is no gap, and they are placed with hammer.

### COLORS

<b>Glue</b>	Red, Green
<b>Modular Rubber</b>	Red, Green, Black

### PRODUCT PACKAGING

<b>Glue</b>	10 KG (9+1) or 24 KG (21+3) Plastic/Metal Buckets.
<b>Modular Rubber</b>	It is properly stacked on the pallets. Protected by plastic packaging.

### PRODUCT STORAGE

<b>Glue</b>	Unopened packages can be stored between +5 and +30 degrees for 12 months.
<b>Modular Rubber</b>	Unopened packages can be stored between +5 and +30 degrees for 12 months.

### PRODUCTION AND INSTALLATION PERIODS

<b>Glue</b>	Production: 1-5 Days	Installation: 1-5 Days	Can not work simultaneously
<b>Modular Rubber</b>	Production: 3-10 Days	Installation: 1-5 Days	Can not work simultaneously

### WARRANTY PERIODS

<b>UV</b>	5 YEARS	% 5 Tolerance
<b>Abrasion</b>	3 YEARS	%10 Tolerance
<b>Installation Warranty</b>	1 YEAR	5 years with maintenance contract

# ANYMATS RT - MODULAR RUBBER

## EXAMPLES OF APPLICATIONS



**anymats®**  
Roll Rubber Floors